

66737



FLOWSTRIP

131231/RE/2

TECHNICAL DATA SHEETPRODUCT REFERENCE : FL1009 DOUBLE SIDED POLYPROPYLENE TAPE/WHITE ADHESIVEDESCRIPTION

A Double Sided Polypropylene tape with an aggressive, pressure sensitive White Rubber adhesive. Has excellent initial tack and adhesion but limited shear properties, temperature performance, UV and plasticiser resistance.

Especially suitable for the affixing of foam backed carpets.

PROPERTIES

Carrier	:	Polypropylene
Adhesive	:	White Rubber Resin
Carrier Thickness	:	25 Micron
Tape Thickness	:	0.15mm (150 micron)
Peel Adhesion to Steel	:	1.7 kg/25mm
Static Shear (1 kg)	:	5 hrs
Liner Release	:	0.03 kg/25mm
Temperature Range	:	-10° to 50°C
Shelf Life	:	1 year in original packaging stored in cool dry conditions

Statements, technical information and recommendations contained herein are based on production data with properties quoted being typical but intended only as a guide. They do not constitute a product specification nor are they to be construed in any manner as warranties expressed or implied.

The User shall determine the suitability of the product for its intended use and the user assumes all risks and liability whatsoever in connection therewith.

Flowstrip Limited, Flowstrip House, Atkinsons Way, Foxhills Industrial Park, Scunthorpe, South Humberside DN15 8QJ, England.
Telephone: 01724 841860 Telefax: 01724 281064